

FEATURES:

- Excellent repeatability and changeability.
- Precise end face inspection by microscope.
- Environmentally stable in optical performance.
- Provide total immunity to electrical interference.
- Optical performance 100% factory tested.
- With ceramic Ferrules.
- Riser &.LSZH cable option.
- RoHS compliant.

APPROVAL:

- Comply with Bellcore, Telcordia GR-326-CORE specification.
- Comply with TIA/EIA-568B.3, ISO11801:2002 and EN50173 specification.

APPLICATIONS:

- Telecom network
- CATV
- Active device termination
- End equipment
- LAN&WAN
- FTTH

TYPICAL PERFORMANCE:

Type	ST	FC	LC	SC	MTRJ
IL (Insertion Loss)	<0.5dB	<0.5dB	<0.5dB	<0.5dB	<0.5dB
Working temperature	-20°C~70°C	-20°C~70°C	-20°C~70°C	-20°C~70°C	-20°C~70°C
Interchange capability (1000 times)	<0.2dB	<0.2dB	<0.2dB	<0.2dB	<0.2dB
Cable Outlet diameter	2.0mm、3.0mm				

SKETCH:



MTRJ



FC



SC



ST



LC

ORDERING INFORMATION:

Part NO: 21vwxyzzzz
Description: Premium-line single-mode fiber optic patch cord
V: mode 1, MM 62.5/125 2, MM 50/125
w: jacket 1: simplex, PVC 2, simplex, LSOH
3, duplex, PVC 4, duplex, LSOH
x, connector 1 1, SC 2, ST 3, FC 4, LC 5, MTRJ
y, connector 2 1, SC 2, ST 3, FC 4, LC 5, MTRJ
zzz: length 010, 1.0m 020, 2.0m 030, 3.0m 050, 5.0m

Premium-Line Systems GmbH. Rosenheimer Str.89 D-83064 Raubling. Germany

► TEL:+49(0)8035 9836 0 ► Fax:+49(0)8035 9836 22



*Picture for reference only